


All claims for error or defective material must be made within 5 days of receipt of goods and prior to installation. Otherwise, said claim will be denied.




| | |
|------------------------|-------------|
| Top Chord Live Load | 20 p.s.f. |
| Top Chord Dead Load | 7 p.s.f. |
| Bottom Chord Live Load | 0 p.s.f. |
| Bottom Chord Dead Load | 10 p.s.f. |
| Total Load | 37 p.s.f. |
| Duration Factor | 1.25 |
| Wind Standard | ASCE7-10 |
| Wind Speed | 140 m.p.h. |
| Building Exposure | C |
| Building Type | Part Closed |

Notice:

It is the responsibility of the building designer or architect to provide an appropriate connection for trusses to supporting structure per reactions shown on truss engineering. Special considerations for mechanical equipment and/or plumbing (and their connections) in truss space must be diagrammed by the builder an approved truss layout prior to

Manning Building Supplies is a truss manufacturer whose responsibilities are limited to those described in ANSI/TPI/WTC 4-2002 (sections 6.0 and 7.0). Accordingly, the construction design, drawings, documents including the installation and bracing of trusses manufactured by Manning Building Supplies.



Typical Truss Ends

PLAN DATE: 5-23-2019

ATTENTION

" APPROVAL OF THIS TRUSS LAYOUT IS NECESSARY BEFORE FABRICATION CAN BEGIN. ACCEPTANCE OF THIS LAYOUT VERIFIES THAT THE SPANS, PITCHES, OVERHANGS, ELEVATIONS, DIMENSIONS, CEILING TRANSITIONS & BEARING CONDITIONS HAVE BEEN CHECKED FOR ACCURACY. ALL TRUSSES WILL BE BUILT IN ACCORDANCE WITH THIS LAYOUT."

APPROVED BY:

DATE:

Warning:

Conventional framing, erection and/or permanent bracing is not the responsibility of the truss designer, plate manufacturer, or truss manufacturer. Persons erecting trusses are cautioned to seek professional advice regarding erection bracing which during erection, and permanent bracing which may be required in specific applications. See "Bracing wood trusses commentary and recommendations (BCSI 2006) for further information.

Trusses shall be installed in a straight and plumb position. Where no sheathing is applied directly to the top and/or bottom chords, they shall be braced as specified on the engineered design. Trusses shall be handled with reasonable care during erection to prevent damage or personal injury.



Manning Building Supplies, INC.

2200 NE 25th Ave.
Ocala, FL 34470-3916

Phone: (352) 387-2572

Fax: (352) 387-2579

WWW.MBS-CORP.COM

OCTRUSS@MBS-CORP.COM

Customer:

ARCHIFENCE INC.

Job Name:

BLACK PRONG

Lot/Blk/Subdiv

1

Reviewed By: Date:

/ /

Drawn By:

Job Number:

OW-19-0660Q

FLORIDA PRODUCT APPROVAL CODES: MITEK PLATES 1999....GEORGIA PACIFIC LVL 2023....GEORGIA PACIFIC WI I-JOIST 1008.... GEORGIA PACIFIC RIMBOARD 2147

TRUSSES LAYOUT
NON SCALE

Client: BLACK PRONG EQUESTRIAN VILLAGE
Address: 450 SE County Road 337
Complements: Bronson, FL 32621 PARCEL NUMBER 0368400100

These plans and project specifications comply with the minimum applicable State of Florida Building Code. (2017 FBC 6th Edition; NEC 2014 electrical code.) and local area building codes and ordinances with respect to current engineering practices.

Engineering/Architect
Florida Registration number:

date:



OWNER

G.Bombonato

DESIGNER/MANAGER

G.Morettoni

ARCHITECT

REVISION DATE

2019/06/21

PROJ DATE

2019/04/26

FILE VERSION

V1.3 - BLACK PRONG.dwg

PAGE

14